

# DS1218RT

This rough terrain scissor lift offers excellent lifting speeds and off-road performance. It is equipped as standard with 4WD and solid non-marking tyres. The stabilisers are automatic and ensure stability when working at height. The platform allows for side-shift at its maximum height, ensuring greater flexibility.



## STANDARD EQUIPMENTS:

- Automatic stabilizers to work at height
- Standard oscillating axle
- Crushing protection
- Self-locking door on the platform
- Speed limit at maximum height
- Platform overload control
- Non-marking tyres
- Tilt indicator with alarm
- Warning siren during lowering and dual flashing LED light
- Safety bracket for maintenance operations
- Horn
- Emergency stop button
- Emergency lowering
- Onboard diagnostics system
- Hour counter
- Proportional controls
- Power to platform
- Fold-down guardrails

## MAIN APPLICATIONS



Maintenance



Plant Service



Construction



Distribution/  
Logistics





Large events

## DS1218RT

Load capacity	454 kg
Load capacity on extended platform	136 kg
Max no. occupants	4
<b>A</b> Working height	12 m
<b>B</b> Platform floor height	10 m
<b>C</b> Overall length (with outriggers)	3.84 m
<b>D</b> Overall width	1.76 m
<b>E</b> Overall height (rails up)	2.59 m
Transport height (rails down)	1.82 m
<b>F</b> Platform size (length/width)	2.88x1.52 m
<b>G</b> Platform extension size	1.43 m
Ground clearance	24 cm
Wheelbase	2.29 m
Turning radius (inside/outside)	2.15 m / 4.85 m
Engine	Kubota D1105-EF02 Stage IV - 18.2 kW 3.000 rpm
Drive motor	-
Lifting motor	-
Travel speed (stowed)	5.2 km/h
Travel speed (raised)	0.48 km/h
Gradeability	40%
Maximum working slope	1.5°/3°
Batteries	12 V / 110 Ah
Integrated charger	-
Hydraulic tank	71 l
Diesel tank	47 l
Tyres	26x12-16.5
Weight (with outriggers)	4,300 kg

**STANDARDS COMPLIANCE:**  
EN 280, ANSI/SAIA A92.20



Automatic stabilizers



On-board diagnostic system